

CEX – IP KVM-1900U series

CAT5 8ports/16ports/32ports 1U rack mount 19" LED KVM drawer over IP



Features

- KVM (keyboard, video, mouse) access over IP and analogous telephone line (modem needed)
- Full control under any OS, in BIOS mode, during boot, at Blue Screen
- 256-bit SSL encryption of all transmitted data and certificate management
- Port to connect a user console for direct analogous access to KVM switch
- Can be used with more standard KVM
- To switch the host computer through the hotkey or OSD menu, which can manage up to 1024 computers
- Password security protection, only authorized users can view and manage on-line computer
- Support a variety of brand industrial computer and the server: EVOC/Lenovo/IBM/DELL/HP/SUN etc.
- Support various operating system: Microsoft, Linux, Unix, etc.

Specifications

Model	IP KVM-1908C	IP KVM-1916C	IP KVM-1932C
Computer connect	Direct: 8	Direct: 16	Direct: 32
	Max: 256	Max: 512	Max: 1024
Keyboard	104 Mechanical mute keyboard		
Mouse	Touchpad		
Switch mode	Hotkey, OSD Menu, Panel Button		
Auto scanning interval	5-99 second		
LCD resolution	1280 x 1024 DDC2B		
Safety performance	Provide access control list function		
Power Input	DC12V input, (AC100-240V 47-63Hz, 35W) optional		
Cable Port	Local console	Keyboard/Mouse/Display (2 x USB + 1 x HDB-15 female)	
	Connector port	8 /16/32 x RJ45 (CAT5 port)	
	Power supply	1 x 3 pin AC power supply socket	
	Remote control	1 x LAN port, 1 x RS232 (LAN port)	
LED Indicator	Power indicator	1	
	Selection indicator	16	
	Boost on-line indicator	16	
	Num Lock	1	
	Caps Lock	1	
	Scroll Lock	1	
Work Environment	Operating Temperature	-10°C~60°C	
	Storage Temperature	-20°C~70°C	
	Humidity	0%-95%RH	
Cabinet Material	High-strength and anti-corrosive steel plate		
Color	Insulated black (optional)		
For Cabinet	800-1040mm		
Net weight	14KG-17KG		
Gross weight	17KG-22KG		
Dimension (L x W x H)	600 x 440 x 44mm		
Package (L x W x H)	738 x 608 x 195mm		
Certificate	CE, FCC, ROHS		