

# CEX – 12.1” HMI Industrial Touch Panel PC’s

IPPC-C1210T (A9)



## • Features

- 12.1” industrial touch panel pc running Linux system
- ARM mother board with Cortex A9
- Memory: 1GB RAM + 8GB Flash
- Aluminum case and fan less design
- 12.1” resistive touch screen

## • Specifications

| Specifications           |   |
|--------------------------|---|
| <b>CPU</b>               | Cortex A9   |
| <b>Display</b>           | 12.1" high-brightness LCD screen; 250cd/m2  |
| <b>Resolution</b>        | 800 x 600   |
| <b>Memory</b>            | 1Gb DDR3 SDRAM  |
| <b>Flash</b>             | 8Gb Flash   |
| <b>Expansion slots</b>   | SD card slot, Max up to 32GB  |
| <b>Network interface</b> | 1 x 100Mbps Ethernet controller   |
| <b>I/O</b>               | <ul style="list-style-type: none"> <li>• 3 x RS232 COM</li> <li>• 2 x RS485 com</li> <li>• 2 x USB2.0 + (1 x USB slave)</li> <li>• 1 x LAN</li> <li>• DC 12V / 24V Power input</li> </ul> |
| <b>Touch Screen</b>      | Resistive touch screen (optional)   |
| <b>Power Supply</b>      | DC 9-24V input. Kindly suggest DC12V or 24VDC power input   |
| <b>Power consumption</b> | 7.5W  |
| <b>Watchdog</b>          | The time can be adjusted  |
| <b>buzzer</b>            | Built-in, provides function control sound;  |
| <b>3G</b>                | WCDMA (optional)  |
| <b>Operating system</b>  | Linux system  |
| <b>Fan less</b>          | Fan less design   |
| <b>Dimension</b>         | 319mm (L) x 259mm (W) x 46.5mm (H)  |
| <b>Installation</b>      | Embedded, Panel type, wall-mount, Table, bracket etc.   |
| <b>Net weight</b>        | 1.8kg   |
| <b>Gross weight</b>      | About 3.5kg   |
| <b>Operating Temp</b>    | -10°C ~ 60°C  |
| <b>Humidity</b>          | -20°C ~ 70°C  |