

# CEX – 12.1” HMI Industrial Touch Panel PC’s

IPPC-A1210T (WIN CE6.0)



## • Features

- 12.1” industrial touch panel pc running Windows CE 6.0/ Linux
- ARM mother board with Cortex A8 1.0 GHz
- Memory: 512M Bytes DDR3 SDRAM + 256M flash
- Aluminum case and fan less design
- 12.1” resistive touch screen

## Specifications

<b>CPU</b>	Cortex A8 1.0GHz
<b>Display</b>	12.1" high-brightness LCD screen; 250cd/m2 brightness
<b>Resolution</b>	800 x 600
<b>Memory</b>	512MB DDR3 SDRAM
<b>Flash</b>	256 flash
<b>Expansion slot</b>	SD card slot, Max up to 32GB
<b>Network interface</b>	1x 100Mbps Ethernet controller
<b>I/O</b>	<ul style="list-style-type: none"> <li>• 3 x RS232 COM, 1 x RS232 (test port)</li> <li>• 2 x RS485 com</li> <li>• 2 x USB2.0 host + (1 x USB slave)</li> <li>• 1 x LAN</li> <li>• 1 x 12V / 24V Power input</li> </ul>
<b>Touch Screen</b>	Resistive touch screen (optional)
<b>Power Supply</b>	DC 9V-24V input, kindly suggest DC12V or 24VDC power input
<b>Power consumption</b>	7.5W
<b>Watchdog</b>	The time can be adjusted
<b>buzzer</b>	Built-in, provides function control sound;
<b>GPRS</b>	Optional
<b>Operating system</b>	Windows CE6.0
<b>Fan less</b>	Fan less design
<b>Dimension</b>	319mm (L) x 259mm (W) x 46.5mm (H)
<b>Installation</b>	Embedded, Panel type, wall- mount, Table, bracket etc.
<b>Net weight</b>	1.8kg
<b>Gross weight</b>	About 3.5kg
<b>Operating Temp</b>	-10°C~60°C
<b>Humidity</b>	-20°C~70°C