

# CEX – 13.1” HMI Industrial Touch Panel PC’s

IPPC-C1330T



## • Features

- 13.3” industrial touch panel pc running Linux system
- ARM mother board with Cortex A9 dual core 1.0Ghz
- Memory: 2GB DDR3 SDRAM + EMMC 8GB flash
- Plastic case and fan less design (Aluminum panel for option)
- 13.3” resistive touch screen

## Specifications

|                          |  |
|--------------------------|--|
| <b>CPU</b>               | Cortex A9 dual core 1.0Ghz   |
| <b>Display</b>           | 13.3" high-brightness LCD screen; 300cd/m2   |
| <b>Resolution</b>        | 1366 x 768   |
| <b>Memory</b>            | 2GB DDR3 SDRAM   |
| <b>Flash</b>             | 8GB flash  |
| <b>Expansion slots</b>   | SD card slot, Max up to 32GB   |
| <b>Network interface</b> | 1 x 100Mbps Ethernet controller  |
| <b>I/O</b>               | <ul style="list-style-type: none"> <li>• 2 x RS232 COM</li> <li>• 2 x RS485 com</li> <li>• 2 x USB2.0 host + (1 x USB slave)</li> <li>• 1 x LAN</li> <li>• DC 12V / 24V Power input</li> </ul> |
| <b>Touch Screen</b>      | Resistive touch screen (optional)  |
| <b>Power Supply</b>      | DC 9-24V. Kindly suggest DC12V or 24VDC power input  |
| <b>Power consumption</b> | 10W  |
| <b>Watchdog</b>          | The time can be adjusted   |
| <b>buzzer</b>            | Built-in, provides function control sound;   |
| <b>Operating system</b>  | Linux system   |
| <b>Fan less</b>          | Fan less design  |
| <b>Dimension</b>         | 357mm (L) x 232mm (W) x 46.2mm (H)   |
| <b>Installation</b>      | Embedded, Panel type, wall-mount, Table, bracket etc.  |
| <b>Net weight</b>        | 2.35kg   |
| <b>Gross weight</b>      | About 3.5kg  |
| <b>Operating Temp</b>    | -10°C~60°C   |
| <b>Humidity</b>          | -20°C~70°C   |