

CEX – Industrial Mini PC

MINI-N6



Features

- Industrial Mini PC with fan less design
- Onboard intel skylake I3 6100U, I5 6200U
- Adopt intel express chipset
- Support MAX DDR4 1866/2133 16G
- 1 x M.2, 1 x 2.5 inches SATA
- 4 x USB 3.0, 2 x USB 2.0, 2 x COM, 1 x HDMI, 1 x DP, 2 x Gigabit LAN, 1 x two-in-one Audio
- Support WIFI/3G/4G (optional, choose 1 from 3)
- Support DC-IN 12V power supply
- Support Windows 7/8/10, Linux system

Specifications

| | |
|------------------------------|--|
| Material | High quality pure aluminum case |
| CPU | Support intel core I3 6100U (dual core, 2.3Ghz, TDP: 15W) Support intel core I5 7200U (dual core, 2.3Ghz, Turbo boost 2.8G TDP: 15W) |
| Chipset | Adopt intel express chipset |
| Memory | Support MAX DDR4 1866/2133 16G (optional) |
| Display | 1 x DP, 1 x HDMI |
| Expansion | Support 1 x MINI-PCIE channel (WIFI / 3G / 4G optional) |
| Storage | 1 x M.2, 1 x SATA 3.0 |
| I/O | <ul style="list-style-type: none"> • 4 x USB 3.0 • 2 x USB 2.0 • 2 x RJ45 10/100/1000M LAN • 2 x COM port, RS232 • 1 x HDMI • 1 x DP • 1 x Two-in-one audio • 1 x power switch |
| WIFI | Optional |
| 3G/4G | Optional |
| BIOS | 64Mb SPI Flash |
| WDT | Support hardware reset (256level, 0-255sec) |
| Power Supply | DC 12V Input |
| OS | Support Windows 7/8/10, Linux system |
| Color | Black (optional) |
| Dimension | 179 x 129 x 55.5mm |
| N.G | 0.65KG |
| Gross weight | About 2KG |
| Operating Temperature | -10°C ~ 60°C |
| Storage Temperature | -10°C ~ 70°C |
| Storage Humidity | 0-90%@40°C (non-condensing) |
| Vibration | 5 grms / 5 ~ 500Hz in working status (SSD) 1 grms / 5 ~ 500Hz in working status (Built-in HDD module) |
| Shock | 50 g peak acceleration (11ms duration) (SSD) 20 g peak acceleration (11ms duration) (Built-in HDD module) |