

CEX – IP KVM-1700C series

CAT5 8ports/16ports/32ports 1U rack mount 17" LED KVM drawer over IP



Features

- KVM (keyboard, video, mouse) access over IP and analogous telephone line (model needed)
- Full control under any OS, in BIOS mode, during boot at Blue Screen
- 256-bit SSL encryption all transmitted data and certificate management
- Port to connect a user console for direct analogous access to KVM switch
- Can be used with most standard KVM
- To switch the host computer through the hotkey or OSD menu, which can manage up to 1024 computers
- Password security protection, only authorized users can view and manage on-line computer
- Support a variety of brand industrial computer and the server: EVOC/Lenovo/IBM/DELL/HP/SUN, etc.
- Support various operating system: Microsoft, Linux, Unix, etc.

Specifications

Model	IP KVM-1708C	IP KVM-1716C	IP KVM-1732C
Computer connect	Direct: 8	Direct: 16	Direct: 32
	Max: 256	Max: 512	Max: 1024
Keyboard	104 Mechanical mute keyboard		
Mouse	Touchpad		
Switch Mode	Hotkey, OSD Menu, Panel button		
Auto-scanning interval	5-99 second		
LCD resolution	1280 x 1024 DDC2B		
Safety performance	Provide access control list function		
Power input	DC 12V input, (AC100-240V 47-63Hz, 35W) optional		
Cable Port	Local Console	Keyboard/mouse/display (2 x USB + 1 x HDB-15 female)	
	Connector port	8 / 16 / 32 x RJ45 (CAT5 port)	
	Power supply	1 x 3 pin AC power supply socket	
	Support Daisy-chain series connectors (8 level)		
LED indicator	Power indicator	2	
	Selection indicator	16	
	Boost on-line indicator	16	
	Num lock	1	
	Caps lock	1	
	Scroll lock	1	
Work Environment	Operating Temperature	-10°C~60°C	
	Storage Temperature	-20°C~70°C	
	Humidity	0%-95%RH	
Cabinet Material	High-strength and anti-corrosive steel plate		
Color	Insulated black (optional)		
For Cabinet	800-1040mm		
Net weight	13KG-17KG		
Gross weight	17KG-22KG		
Dimension (L x W x H)	568 x 480 x 44mm		
Package (L x W x H)	708 x 608 x 195mm		
Certificate	CE, FCC, ROHS		