

CEX – KVM-1900M series

8ports/16ports 1U rack mount 19" LED KVM drawer over IP



Features

- KVM (keyboard, video, mouse) access over IP and analogous telephone line (modem needed)
- Full control under any OS, in BIOS mode, during boot, at Blue Screen
- 256-bit SSL encryption of all transmitted data and certificate management
- Port to connect a user console for direct analogous access to KVM switch
- Can be used with more standard KVM
- To switch the host computer through the hotkey or OSD menu, which can manage up to 512 computers
- Password security protection, only authorized users can view and manage on-line computer
- Support a variety of brand industrial computer and the server: EVOC/Lenovo/IBM/DELL/HP/SUN etc.
- Support various operating system: Microsoft, Linux, Unix, etc.

Specifications

Model	IP KVM-1908M	IP KVM-1916M
Computer connect	Direct: 8	Direct: 16
	Max: 256	Max: 512
Connector port	8/16 x HDB-15 female (yellow)	
IP Module console	1 x RJ45 port, 1 x VGA port (male), 1 x USB	
Selection connection	Support daisy-chained serial connection (8 levels) and stacking cascade connection (2 levels)	
Keyboard	104 Mechanical mute keyboard	
Mouse	Touchpad	
Switch mode	Hotkey, OSD Menu	
Auto scanning interval	5-99 second	
Power Input	DC12V input, (AC100-240V 47-63Hz, 35W) optional	
Led Indicator	Power Indicator	2
	Selection Indicator	16
	Boost on-line Indicator	16
	Num Lock	1
	Caps Lock	1
	Scroll Lock	1
Work Environment	Operating Temperature	-10°C~60°C
	Storage Temperature	-20°C~70°C
	Humidity	0%-95%RH
Cabinet Material	High-strength and anti-corrosive steel plate	
Color	Insulated black (optional)	
For Cabinet	800-1040mm	
Net weight	15KG-18KG	
Gross weight	18KG-22KG	
Dimension (L x W x H)	610 x 480.4 x 44mm	
Package (L x W x H)	738 x 608 x 195mm	
Certificate	CE, FCC, ROHS	